



(SKC) COTES CARACTERISTIQUES SPECIALES
SPECIAL KEY CHARACTERISTICS

INDICATION DIMENSIONS S.P.C
DENOTES S.P.C DIMENSIONS

INDICATION DIMENSIONS CRITIQUES
DENOTES CRITICAL DIMENSIONS

INDICATION DIMENSIONS FONCTIONNELLES
DENOTES FUNCTIONAL DIMENSIONS

QUANTITE PAR FEUILLE INDIVIDUELLE
QUANTITY PER INDIVIDUAL SHEET

1 0 4 (SKC) 0

NOTE :
- MARKING "A" is used to identify "STANDARD" terminal
- CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm
1	BODY TERMINAL	high conductivity copper alloy thickness=0.2 mm
MARK	DESIGNATION	MATERIAL

PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm ²)	A=0.2	B=0.2	rC ^{+0.15} _{-0.1}	D=0.2	E=0.2	rF=0.1	WEIGHT (g)
0643221029	Sn	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221219	Au 1.27μ MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221039	Sn	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221239	Au 1.27μ MINI	Sn	Ni								
0643221019	Sn	Sn	Ni								
0643221229	Au 1.27μ MINI	Sn	Ni								

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS: mm SCALE: 20:1

GENERAL TOLERANCES (UNLESS SPECIFIED):
ANGULAR TOL ± 2.0°
4 PLACES ± 0.1
3 PLACES ± 0.1
2 PLACES ± 0.1
1 PLACE ± 0.1
0 PLACES ± 0.1

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: NX RE-MASTERING

EC NO: 114689
DRWN: SSUVARNA 2017/07/05
CHK'D: SLAFAURE 2018/06/04
APPR: SLAFAURE 2018/06/14

INITIAL REVISION:
DRWN: FPAROLARI 2007/09/17
APPR: LSTICKEIR 2007/09/17

FIRST ANGLE PROJECTION DRAWING SERIES: A1-SIZE 64322

MATERIAL NUMBER: SEE CHART CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 1

DOCUMENT NUMBER: SD-64322-001 DOC TYPE: PSD DOC PART: 000 REVISION: E1

PRODUCT CUSTOMER DRAWING

CP RCPT TRM 0.6